



## STICTION ELIMINATOR® ENGINE RESTORATIVE + FR3® NANO-LUBRICANT

### PRODUCT OVERVIEW

Stiction Eliminator® safely removes and prevents the gummy, sticky residue that builds up inside diesel injectors over time. It cleans and lubricates the entire oil side of the engine: injectors, turbo, rings, oil pump, everything the oil touches.

### BENEFITS

Stiction Eliminator® is guaranteed to remove stiction within 4,000 miles. The most noticeable improvements are on hesitation, fuel mileage, power, and the turbo.

Restores 9 out of 10 fuel injectors diagnosed as "failed"	Cleans turbo, rings and oil pump
Improves power and compression	Removes engine deposits
Seals Rings	Neutralizes harmful engine acids
Reduces frictional drag	Prevents excessive wear
Reduces lifter and valve noise	Restores oil pressure
Reduces blow-by	Fortifies existing oil to help it work more effectively

### APPLICATIONS AND USES

Stiction Eliminator® is safe and effective for use in all diesel and gasoline engines: semi-trucks, pick-up trucks, farm equipment, and autos. These include but are not limited to Ford Powerstroke, Dodge Cummins, GM Duramax, Saab, Volkswagen, Audi, Caterpillar, and Detroit.

Use Stiction Eliminator® to treat or prevent hard starts, hesitation, excessive black smoke, poor acceleration, rough idling, or failing injectors.

### DIRECTIONS FOR USE

Stiction Eliminator® is most effective when used with a fresh oil change and is safe to leave in for the life of the oil. Synthetic oil is recommended but not required.

Use approximately 4 OZ per 1 QT of oil for initial cleanup, 2 OZ per 1 QT of oil for maintenance. Add STICTION ELIMINATOR® during a fresh oil change and leave in during entire oil change interval.

**Maintenance treatment:** A half dose at every third oil change is recommended for prevention.

### PACKAGING

Stiction Eliminator® is available in a:

- 16 ounce round bottle
- 32 ounce (1-quart) round bottle
- 64 ounce (2-quart) round bottle
- 1-gallon jug
- 5-gallon jug
- 55-gallon drum
- 275-gallon tote

Engine Oil Capacity	STICTION ELIMINATOR® Initial Treatment
4-6 quarts	16 ounces (1/2 qt)
7-10 quarts	1 quart
11-20 quarts	2 quarts
21-35 quarts	3 quarts
36-48 quarts	4 quarts



## STICTION ELIMINATOR® ENGINE RESTORATIVE + FR3® NANO-LUBRICANT

### TYPICAL PROPERTIES

Property or Test	Result
API gravity @ 60°F	15.32
Viscosity @ 100°F	13,000 SUS
Viscosity @ 210°F	1,100 SUS
Flash point (COC)	122 °F
Pour point	-40 °F
1-H test (M2C101B)	Pass
Acid test	Excellent
Color	Dark green
Copper strip corrosion test	Pass - Class 1
Humidity cabinet test	Pass
Gum and varnish test	Excellent
Moisture test	Excellent

The Safety Data Sheet is available at [hotshotsecret.com/print-documents](https://hotshotsecret.com/print-documents)

Manufactured by Lubrication Specialties, a wholly owned subsidiary of 